

CPA

CPA SERIES LOW PROFILE COMPRESSION LOAD CELLS



Stainless steel compression load cells suitable for extremely harsh environments.

CAPACITIES (kg): 150, 300, 500, 1000, 2000, 3000, 5000, 7000, 10000.

OIML R60, C3 precision class from 2000 a 10000kg.

Stainless steel. IP68 protection.

The best solution
for advanced industrial
applications

MAIN FEATURES






- CAPACITIES from 150 to 10000 kg
- OIML C3 CLASS, from 2000 to 10000 kg
- LOW PROFILE
- GREAT RESISTANCE TO LATERAL FORCES
- STAINLESS STEEL CONSTRUCTION
- IP68 PROTECTION
- SHIELDED CONNECTION CABLE

TECHNICAL FEATURES

- Minimum load cell verification interval: $V_{min} = E_{Max} / 10000$
- Full Scale Output: 2mV/V +/- 0,1%
- Repeatability: 0,01% F.S.
- Temperature effect on zero: 0,001% /°C
- Temperature effect on full scale output: 0,0013% /°C
- Compensated Temperature Range: -10°C/+40°C
- Operating Temperature Range: -30°C/+85°C
- Creep error after 4 hours: 0,03% F.S.
- Maximum tolerated excitation voltage: 15 Vdc
- Input Resistance: 1100 ± 10% Ohm
- Output Resistance: 1000 ± 10% Ohm
- Zero Balance: ± 2% F.S.
- Insulation Resistance: >5000 MOhm
- Safe Overload: 150% F.S.
- 6-wire shielded cable, 5 mm diameter:
 - 5 m long for the versions from 150 up to 10000kg

VERSIONS

Available versions

Codice	Max (kg)
CPA150	150
CPA300	300
CPA500	500
CPA1000	1000
CPA2000 	2000
CPA3000 	3000
CPA5000 	5000
CPA7000 	7000
CPA10000 	10000



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784



SALES AND TECHNICAL ASSISTANCE SERVICE