

JBQAI

"JBQAI": EQUALISED JUNCTION BOX FOR ATEX ENVIRONMENTS



Stainless steel junction box with IP66 protection from water and dust, and fitted with an intrinsically safe electronic board for junction and equalisation of load cells. Terminal boards with screws for easing th connection of the load cells and signal adjustment trimmer, for an accurate and reliable equalisation. Marking: ATEX II 2G Ex ib IIC T6 Gb for gases. ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

Working in cooperation with:

UAB DESKA

PRAMONES 5 - LT-94102 - KLAIPEDA - LITHUANIA Tel. 00370-46-381089 Fax. 00370-445-76466 info@deska.lt The best solution for advanced industrial applications

TECHNICAL FEATURES

- Designed and made according to the ATEX directive, group II category 2GD, according to the IEC/EN60079-0, IEC/EN60079-11, and IEC/EN60079-31 norms.
- Stainless steel case.
- PG9 metallic cable gland.
- Protection degree: IP66.
- Dimensions: 190x130x45mm (lxwxh).

NOTE: the dimensions are not compatibles for mounting on 4 load cells platforms/pallet weighers.

ATEX PARAMETERS OF THE JUNCTION BOX

- Uo = Ui = 24Vdc
- Io = Ii = 174mA
- Co = Ci = OmF
- Lo = Li = 0mH

or

- Uo = Ui = 12Vdc
- Io = Ii = 3,33A
- Co = Ci = OmF
- Lo = Li = OmH





DINI ARGEO FRANCE sarl Nogent-sur-Marne DINI ARGEO GMBH Sinsheim - Germany DINI ARGEO UK Ltd Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd Shanghai - China DINI ARGEO WEIGHBRIDGES Calto (RO) – Italy



HEAD OFFICE Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy



UAB DESKA

PRAMONES 5 - LT:94102 - KLAIPEDA - LITHUANIA Tel. 00370-46-381089 Fax. 00370-445-76466 info@deska.lt

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.