

# RL5416DC

Digital Stainless Steel, Hermetically Sealed, C4, IP68



## Specifications

**Transmission Speed:**  
100 kHz (max)

**Current Consumption:**  
35 mA

**Conversions Per Second:**  
40 s

**Material Finish:**  
Stainless steel

**Certified Temperature:**  
-10° C to 40° C

**Operating Temperature:**  
-35° C to 70° C

**Seal Type:**  
Hermetically sealed, IP68

**Rated Excitation:**  
15V

**Vmin:**  
Emax/15000

**Insulation Resistance:**  
>5.000 megohms

**Cable Length:**  
4 m, 7 m, 9 m, 15 m, 25 m, 50 m

**Cable Construction:**  
PVC

**Warranty:**  
Two-year limited warranty

## Order Information

Picture is a representation of actual product

Load Rating	Part #	Price
30t	195843	Consult
40t	195844	Consult

Cables					
1 Connector			2 Connector		
Length	Part #	Price	Length	Part #	Price
15 m	182733	Consult	4 m	182736	Consult
25 m	182734	Consult	7 m	182737	Consult
50 m	182735	Consult	9 m	182738	Consult

## Options

Picture is a representation of actual product

Part #	Description	Price
173798	Stainless steel cup set	Consult

## Dimensions

Rated Capacity	A	B	C	D	E	F	G	H
mm								
30 - 40t	150	88	Ø89	Ø44	25	36	32	Ø84

