



Bench and floor scales with column, characterized by multifunction weight indicator, completely stainless steel structure. Easy to use and versatile, guaranteeing precision and reliability. Particularly suitable for industrial and commercial use. Available also in CE-M approved version according to OIML R-76 / EN 45501 standards.

Working in cooperation with:

UAB DESKA

PRAMONES 5 - LT-94102 - KLAIPEDA - LITHUANIA
Tel. 00370-46-381089 Fax. 00370-445-76466
info@deska.lt

**The best solution
for advanced industrial
applications**

TECHNICAL FEATURES

- Weight indicator with waterproof IP65 STAINLESS STEEL case. Backlit 25mm LCD display with 6 high contrast digits and icons for indication of active functions. Waterproof 5-key functional keypad.
- Functions with an aluminium load cell, protected in IP65 stainless steel cover, approved according to OIML R60 C3 standards (3000 divisions).
- Stainless steel structure, with adjustable resting feet and level.
- Stainless steel loading surface, size: see the table.
- Support column, height:
 - 350 mm in the "T" models;
 - 500 mm in the "Q" models;
 - 700 mm in the "X" models.
- Digital calibration and set-up from keypad or from PC with DINITOOLS.
- Power supply: 230 Vac power supplier.

SELECTABLE FUNCTIONS

- X 10 high resolution visualisation
- Net/Gross or lb/kg conversion
- Weighs totalisation
- Formulation
- Counting
- +/- Check
- Percentage weighing
- Alibi (with optional interface)
- HOLD (freezing the weight on the display)

KEYBOARD AND PRINTING FUNCTIONS

- KEYBOARD: Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching.
- PRINTING: Configurable print layout with:
 - 4 heading lines
 - Gross-Tare-Net and ticket number
 - Date and time (only with DFCLK)
 - Print of barcode 39.

I/O SECTION

- RS232/RS485 port for connection to PC, PLC or repeater.
- RS232 port configurable for connection to printer.
- IR input for managing the remote control.

VERSIONS

Available versions

| Codice | l x w x h (mm) | Max (kg) | d (g) | M (g)* |
|-----------|-------------------|-------------|----------|------------------|
| WETI15-1 | 300x300x130 | 15 | 5 | 5 |
| WEQI30-1 | 400x400x140 | 30 | 10 | 10 |
| WEQI150-1 | 400x400x140 | 150 | 50 | 50 |
| WEXI60-1 | 600x600x150 | 60 | 20 | 20 |
| WEXI150-1 | 600x600x150 | 150 | 50 | 50 |
| WEXI300-1 | 600x600x150 | 300 | 100 | 100 |

(*) These divisions are obtainable only with the relative options



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy



UAB DESKA

PRAMONES 5 - LT-94102 - KLAIPEDA - LITHUANIA

Tel. 00370-46-381089 Fax. 00370-445-76466

info@deska.lt

SALES AND TECHNICAL ASSISTANCE SERVICE